



MOSQUITO MAGNET®

Advanced Mosquito Defense Systems

DOMESTIC - KEEP OUT OF REACH OF CHILDREN
READ THE LABEL BEFORE USING

Please retain these Operating Instructions for future reference.
REG. NO. 29943 PCPA



Leader in 360° Customer Support

- Customer Care Hotline: 1-800-953-5737
- Online Assistance Available
- Certified Service Locations

INDEPENDENCE™

Woodstream Canada Corporation
25 Bramtree Court, Unit 1
Brampton, Ontario Canada L6S 6G2
Tel: (800) 800-1819
www.mosquitomagnet.com

For Outdoor Use Only
1440-638

Operation Manual

GAS-FIRED
UL US CE
LISTED
Gas Fired Insect
Control Equipment
47 WB

Welcome

Congratulations on your purchase of Mosquito Magnet®. Now you can begin to enjoy your outdoor living space again.

Mosquito Magnet® is the #1 mosquito trap in North America. Backed by 18 years of research and independent testing, Mosquito Magnet® is scientifically proven to effectively reduce mosquitoes & other biting insects from your yard.

Mosquito Magnet® is easy to use. The link www.mosquitomagnet.com/videos, provides key information for getting started. In this manual, you'll learn everything you need to know about how it works, optimal trap placement, maintenance, storage and warranty information. The keys to success are trap placement, utilization of the correct attractant for your area and routine maintenance. For optimal catch rate, you'll need to change the propane tank and attractant every 21 days.

Our Customer Care line is available to answer all your questions regarding your new purchase. Please feel free to contact us...

Customer Care: 1-800-953-5737

Visit us online at www.mosquitomagnet.com for additional information regarding Mosquito Magnet® tips, testimonials, and additional product offerings.

Woodstream® Corporation

69 North Locust Street
Lititz, PA 17543
1-800-953-5737
www.mosquitomagnet.com

The Mosquito Magnet® traps are covered by one or more of the following patents:

USA Nos. 5,813,166; 6,145,243; 6,286,249; 6,817,140;
6,840,005; 6,848,466; 6,892,492; 7,074,830; 7,243,458;
7,281,351; 7,293,387; 7,536,824; 7,614,180; 7,752,803;
7,987,631; 8,067,469; 8,051,601 and 8,141,291

Other patents pending

Made in China

FOR YOUR SAFETY

If you smell gas:

1. Shut off the gas to the appliance.
2. Extinguish any open flame.
3. Open lid.
4. If odor continues, immediately call your gas supplier or your fire department.

FOR YOUR SAFETY

1. Do not store or use gasoline or other flammable vapors and liquids in the vicinity of this or any other appliance.
2. An LP cylinder not connected for use shall not be stored in the vicinity of this or any other appliance.



MOSQUITO MAGNET®

Contents

Welcome/Contents	1-2
Safety Instructions	3-4
Principle Parts	5
Assembly Instructions	6
Set-Up	7-9
Bug Bag Installation	
Charging Instructions	
Trap Placement	
Propane Tank Installation	
Octenol Attractant Installation	
Instructions	10
Starting Instructions	
Shut Down Instructions	
When Not In Use	
End of Season Storage	
For Best Results	
Maintenance	11
Maintenance	
Propane Tank Changing Tips	
Maintenance Schedule	
Troubleshooting	12
Limited Warranty	13

Questions or Comments

Please contact Woodstream® Corporation if you have any questions or experience any problems with your Mosquito Magnet®:

1-800-953-5737

Woodstream® Corporation
69 North Locust Street
Lititz, PA 17543

www.mosquitomagnet.com

Model No.:	Independence™
Serial No.:	
Type of Gas:	Propane
Manifold Pressure:	100 – 110 psi
Minimum Gas Supply Pressure:	11.0 in. WC
Input Rating:	759 Btu/Hr.
Minimum Clearances:	20 – 24”



How the Mosquito Magnet® Works

Mosquitoes and other biting insects use the long-range attractant carbon dioxide (CO₂) to locate people. Once in close proximity, mosquitoes use short-range attractants such as scents emitted from the skin, to determine which person they are going to bite. The Mosquito Magnet® mimics a human by converting propane to CO₂, with its patented catalytic conversion technology, in combination with a short-range attractant.

Attracted by the CO₂ and short-range attractant, mosquitoes and other biting insects are drawn to the Mosquito Magnet®. When they reach the trap, the insects are vacuumed into a bug bag by our patented Counterflow Technology™, where they dehydrate and die within 24 hours.

The Mosquito Magnet® is silent, odorless and runs 24/7. When properly placed in your yard, the **trap begins working immediately. Noticeable results can be achieved in 7 to 10 days.** To greatly reduce your biting insect population, allow 4 weeks. Leave the Mosquito Magnet® out all summer long, to control the mosquito population in your yard.

Only biting insects are targeted including mosquitoes, no-see-ums, black flies and midges. Beneficial insects such as butterflies, bees or moths are not targeted.



MOSQUITO MAGNET®

Safety Instructions

Please read and follow all safety instructions and warnings.

Children and adults should be alerted to the hazards of high surface temperatures and should stay away to avoid burns or clothing ignition.

Young children should be carefully supervised when they are in the area of the trap. Keep out of reach of children.

Clothing or other flammable materials should not be hung from the trap, or placed on or near the trap.

Note: Some or all of the following required safety instructions for propane powered devices may apply to your trap. Allow trap to cool for 5 minutes before re-starting.

Warning: Improper installation, adjustment, alteration, service or maintenance can cause injury or property damage. Read the installation, operating and maintenance instructions thoroughly before installing or servicing the trap.

Caution: The gas pressure regulator provided with this appliance must be used. This regulator is set for an outlet pressure of 11.0 in. Water Column. The minimum inlet gas supply pressure is 11.0 in. Water Column from regulator.

- This unit is not intended to be installed in or on recreational vehicles and/or boats.
- The gas supply must be turned off at the LP-Gas supply cylinder when this appliance is not in use.
- The installation must conform with local codes or, in the absence of local codes, with the National Fuel Gas Code, ANSI Z223. 1-1998 for US and with the CAN1-B149 for Canada.
- To test for a gas leak, place soapy water around the connector, regulator, and gas hose assembly. If bubbles appear, there is a gas leak.
- Inspect the hose before each use of the unit. If it is evident there is excessive abrasion or wear, or the hose is cut, it must be replaced prior to the unit being put into operation. The replacement hose shall be that specified by the manufacturer.
- The trap is equipped with an internal spark ignition device. Failure to follow starting procedure will result in the trap not starting.
- Installation and repair should be done by a qualified service person (find service centers on www.mosquitomagnet.com). The heater should be inspected before use and at least annually by a qualified service person. More frequent cleaning may be required as necessary. It is imperative that the control compartment, burners, and circulating air passageways of the trap be kept clean.



MOSQUITO MAGNET®

Safety Instructions

- Maintain adequate clearances of 20"–24" around air openings into the combustion chamber, clearances from combustible material, provisions for accessibility and for combustion and ventilating air supply. Keep the trap area clear and free from combustible materials, gasoline, and other flammable vapors and liquids. The appliance is not to be used in locations where flammable vapor or explosive dust is likely to exist.
- Do not obstruct the flow of combustion and ventilation air.
- Keep the ventilating openings of the cylinder enclosure free and clear from debris.
- Clean the trap with a damp cloth, if necessary.
- A maximum of a 20 lb LP-Gas cylinder shall be used.
- The LP-Gas cylinder must be provided with a shut-off valve terminating in an LP-Gas supply cylinder valve outlet specified for Connection No. 510 in the Standard for Compressed Gas Cylinder Valve Outlet and Inlet Connections, ANSI/CGA-V-1-1977.
- The LP-Gas cylinder supply system must be arranged for vapor withdrawal and the cylinder must include a collar to protect the cylinder valve.
- The LP-Gas cylinder used shall be constructed and marked in accordance with the specifications for LP-Gas cylinders of the U.S. Department of Transportation (DOT) or The National Standard of Canada CAN/CSA-B339.
- The trap shall be used outdoors only in a well ventilated space and shall not be used in a building, garage, or any other enclosed area.
- The LP-Gas cylinder must be disconnected and removed from the appliance, if the appliance is stored indoors.
- LP-Gas cylinders must be stored outdoors in a well-ventilated area out of reach of children.
- Disconnected cylinders must have threaded valve plugs tightly installed and must not be stored in a building, garage, or any other enclosed area.
- The pressure regulator and hose assembly supplied with this appliance must be used for connection to the LP-Gas cylinder. Replacement pressure regulators and hose assemblies must be specified by the manufacturer.
- Avoid improper use of extension cords. Keep connections away from moisture and avoid damage to the cord.
- If the supply cord is damaged, it must be replaced by the manufacturer or its service agent or a similarly qualified person in order to avoid hazard.

Please contact Customer Care
if you have any questions at:

1-800-953-5737


or visit www.mosquitomagnet.com

⚠ Warning: SHOCK! An electric shock hazard may exist if water from a garden hose is directed at the Mosquito Magnet®. Route the power cord in the safest possible manner to avoid personal injury.



MOSQUITO MAGNET®


Principle Parts




Parts Included

Mosquito Magnet Octenol Biting Insect Attractant


EPA Reg. No. 72563-1 (Short-Range Attractant)



Bug Bag



4 "C" Batteries



"C" Size Batteries recommended:


- Micropower
- Panasonic Extreme Power
- Duracell Ultra
- Energizer Ultra +



Assembly Instructions


Trap Assembly:

Step 1




Place base upside down on a flat surface, unfold U-shaped support leg until it locks in place.

Step 2



Turn base and leg assembly right-side-up and place support pole into cavity in base.


Step 3



Place trap power head onto pole. Press down firmly with two hands to secure.


Assembled trap should have the front of power head/trumpet placed farthest from the wheels in the same direction as base U-shaped legs.

Step 4




Open battery door in the rear of the trap.

Step 5



Place four (4) "C" batteries in the battery cage. Insert battery cage connector in the power receptacle until it latches, then insert the battery cage in the opening.

Step 6



Close battery door when complete (snaps into place).



MOSQUITO MAGNET®


Set-Up

Bug Bag Installation:

Reach in the bug bag and fully open the drawstring entrance before installing. This will help optimize the airflow which will enhance the performance of your trap.

Lift clear plastic lid and lock plastic holding bracket of bug bag into front of compartment. Close plastic lid when finished.


Note: Fabric loops hook over plastic posts allowing bug bag to expand to its highest capacity.



Bug bag locks into front of compartment

Trap Placement

1. Determine the direction of the prevailing wind. Check local weather patterns if you are unsure.
2. Stand in the center of the area you are trying to protect and look toward the prevailing wind.
3. Proper placement of the trap will be 30 – 40 feet in front of you, within 5-6 feet of ground cover (i.e. bushes, flowerbeds, tree line, marshbed). Ensure that trap is not directly against any blockades such as buildings, fences, etc.
4. It is recommended that the trap be placed in the shade.
5. Do not place trap directly above a water source (sprinklers, hose, etc.).
6. Trap must be placed on level ground to avoid tipping or uneven propane distribution.
7. For optimal trap placement in your yard, refer to the instructional video at www.mosquitomagnet.com/videos to build your own yard diagram for correct trap placement.




Set-Up

Propane Tank Installation


1. After trap is placed in its ideal location, place propane tank onto the molded cradle.
2. Make sure propane tank is fully closed. Attach propane regulator hose to propane tank. Secure tightly by hand. ***Do not use tools.***
3. Turn propane on by slowly turning valve counter-clockwise. Take care not to turn too quickly to avoid engagement of safety valve.

⚠ DO NOT MOVE TRAP WITH TANK ATTACHED!
TANK MUST BE DISCONNECTED FROM REGULATOR BEFORE TRAP IS RELOCATED TO AVOID DAMAGE TO REGULATOR AND/OR TRAP. BE ADVISED, DAMAGE CAUSED FROM FAILURE TO COMPLY WITH THIS INSTRUCTION IS NOT COVERED UNDER WARRANTY.


Step 1 - Propane Tank Placement



Step 2 - Attach Regulator



Step 3 - Slowly Open Valve



MOSQUITO MAGNET[®]

Set-Up

Octenol Attractant Installation

1. Locate Mosquito Magnet® Octenol Biting Insect Attractant. Remove mosquito attractant packet from bag. Carefully peel back foil cover
2. Locate the Octenol carrier compartment inside the plume tube. Turn cap counter-clockwise about 1/8 turn. Remove end cap.
3. Place the open packet of mosquito attractant into the carrier compartment.
4. Replace end cap on carrier compartment. Be sure to align cap's "feet" with grooves inside carrier compartment. Secure cap by turning clockwise until it clicks (about 1/8 turn).

Precautionary Statements

Hazards to Humans and Domestic Animals.

Caution: Harmful if swallowed. Avoid contact of skin, eyes or mouth with the evaporation holes. Wash hands before eating, drinking, chewing gum, using tobacco or using bathroom facilities.

First Aid

If swallowed

- Call poison control center or doctor immediately for treatment advice.
- Have person sip a glass of water if able to swallow.
- Do not induce vomiting unless told to do so by the poison control center or doctor.
- Do not give anything by mouth to an unconscious person.

If on skin or clothing

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

If in eyes

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

If inhaled

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible.
- Call a poison control center or doctor for treatment advice.

Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

Environmental Hazards: Do not apply directly to water. Do not contaminate water when disposing of equipment washwaters or rinsate.

Directions for Use

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

Replace cartridge every 21 days* (Note: After 21 days of use, cartridge appears the same; however, it will no longer be effective as the octenol will have been released.)

*Based on release rate studies conducted at a constant ambient air temperature of 80° F for 21 days. Octenol release from this product will be more rapid at higher ambient air temperature.

Storage & Disposal

Do not contaminate water, food or feed by storage or disposal.

Storage: Store unopened attractant cartridge in a cool, dry place. Discard outer plastic bag in trash.

Disposal: Do not reuse attractant cartridge. Dispose of used attractant cartridge in the trash.

Step 1



Step 2



Step 3



Step 4



Instructions

****READ MANUAL BEFORE STARTING****

Starting Instructions

It is recommended that you read the entire manual before starting the Mosquito Magnet® trap.

1. Insert Octenol or Lurex3 cartridge in compartment per instructions in cartridge packaging.
2. Install 4 “C” Batteries into the rear compartment..
3. Connect regulator to propane tank.
4. Slowly turn propane tank valve on.
5. Push “ON/OFF” switch to ON position. LED light will turn solid orange indicating warm-up. After 15-25 minutes, trap LED light will turn solid green indicating the trap is running at full capacity.

Shut Down Instructions

To turn off the trap, press the ON/OFF button. RUN will show on the display. COOL and the indicator arrows will flash on the display. The LED will be green. After a two minute cool down, the fan will stop, the LED will turn off and OFF will show on the display.

When Not In Use

If the unit is not in use, the gas must be turned off at the supply cylinder. Storage of this unit indoors is permissible only if the cylinder is disconnected and removed. Cylinders must be stored outdoors, out of reach of children and must not be stored in a building, garage or any other enclosed area.

End of Season Storage


Push ON/OFF switch to OFF position to shut down the trap. The LED light will go out and the fan will continue running until trap is cool. Close the propane tank valve and disconnect regulator.

Any open Mosquito Magnet® attractant should be removed and discarded. See attractant label for disposal instructions. The bug bag should also be discarded prior to storing the trap.

STORAGE: The trap should be stored indoors in a garage or shed in the off-season. Cover trumpet to prohibit insects from nesting. Cover unit with a tarp and secure tightly at the bottom to keep out dust, spider webs and other debris.

For Best Results (unit must run for 24 hours/day)

- Your trap will begin capturing immediately with significant reduction in the mosquito population in 7-10 days. Allow 4 weeks to significantly reduce the mosquito population in your yard.



- Allow trap to cool for 5 minutes before re-start.
- Never spray insecticide in or around trap.
- Trap can be left running in the rain.
- If using lime or fertilizer compounds, be sure to shut down the trap first to prevent dust or fine mist from being drawn into trap and clogging bug bag.

Warning: Improper installation, adjustment, alteration, service or maintenance can cause injury or property damage. Read the installation, operating and maintenance instructions thoroughly before installing or servicing this equipment.

Caution: The gas pressure regulator provided with this appliance must be used. This regulator is set for an outlet pressure 11.0 in. water column.

The gas supply must be turned off at the LP-Gas supply cylinder when this appliance is not in use.

Leader in 360° Customer Support

- Customer Care Hotline: 1-800-953-5737
- Online Product Registration Available
- Visit www.mosquitomagnet.com for Troubleshooting Tips/Trap Placement
- Certified Service Locations – Information Available at www.mosquitomagnet.com



MOSQUITO MAGNET®

Maintenance

Maintenance

• ***21 Day Maintenance Cycle***

- Refill propane. (Propane lasts approximately 21 days with 24-hour/7-days operation.)
 - Replace short-range attractant cartridge.
See Mosquito Magnet® attractant label for instructions.
 - Empty or replace bug bag.
- Periodically wipe down the outside of the trap with a clean, damp cloth.

Propane Tank Changing Time

When attaching the regulator knob to a tank after a tank change, be sure to fully tighten the regulator knob onto the tank. No need to use tools, but do turn the knob as far as possible by hand. When this is done, loosen the knob 1/4 turn, then re-tighten to maximize seal.

The purpose for this is to fully engage the regulator onto the tank. If the regulator is not fully engaged, the flow of gas may be restricted to the point where the trap will show a gas empty code. If this occurs, press the off button, close the tank valve, and remove the regulator from the tank. Re-attach the regulator and try again.



MOSQUITO MAGNET®

Troubleshooting

Problem	Possible Cause	Solutions
<p>Unit won't start</p> <p>RED LED light flashing at 7 second intervals</p>	<ol style="list-style-type: none"> 1. Propane tank may be empty. 2. If propane tank is new and has been newly filled it must be purged. 3. There could be a loose connection. 4. Bug bag may be full or clogged. 	<ol style="list-style-type: none"> 1. Weigh tank and check against "empty" weight. Written on tank. 2. Bring tank to filling location. Air may be in fuel line. Ask for tank to be purged. <i>Hint: If you have another propane powered device operating on a standard, 20 lb propane tank, try hooking that tank up to the trap to verify that the issue is with your tank.</i> 3. Verify all connections. Make sure propane tank valve is fully open. 4. Replace the bug bag.
<p>Unit won't stay running</p>	<ol style="list-style-type: none"> 1. 'Possible Causes' 1 & 3 above may apply. 2. Regulator is not fully engaged. 	<ol style="list-style-type: none"> 1. Go through above steps 1 & 3. 2. See Tank Changing Tips on page 8.
<p>Low or No Catch</p>	<ol style="list-style-type: none"> 1. Insects may not be out yet. 2. Trap placement issue. 3. Biting insect reproductive cycles have not yet been broken. 4. Counterflow may be disrupted. 	<ol style="list-style-type: none"> 1. Verify temperature is consistently over 50°F (10°C). 2. Follow steps in the "Trap Placement" section of your owner's manual. 3. Keep trap in constant operation 24 hours/day, 7 days per week for at least 4 weeks to reduce the mosquito population. 4. Air flow may be restricted. Contact your Local Service Provider.
<p>LED Flashing alt RED/GREEN at 7 second intervals</p>	<ol style="list-style-type: none"> 1. High Temperature. 	<ol style="list-style-type: none"> 1. Turn off trap and allow to cool for 1/2 hour. Then restart.
<p>LED Flashing alt RED/ORANGE at 7 second intervals</p>	<ol style="list-style-type: none"> 1. Battery Voltage Low. 	<ol style="list-style-type: none"> 1. Make sure the 4 "C" batteries are properly installed and fresh. 2. Ensure the battery cage connector is properly installed. 3. After several repeated unsuccessful attempts, replace with 4 new "C" batteries.
<p>Double flashing RED LED at 7 second intervals</p>	<ol style="list-style-type: none"> 1. Thermister Fault. 	<ol style="list-style-type: none"> 1. Contact your Local Service Provider or call Consumer Care at: 1-800-953-5737.
<p>LED light solid RED</p>	<ol style="list-style-type: none"> 1. Electrical Fault. 	<ol style="list-style-type: none"> 1. Contact your Local Service Provider or call Consumer Care at: 1-800-953-5737.



Limited Warranty

Limited Warranty

This warranty, (1) year from the purchase of the unit, is extended only to the original purchaser/user of products. This limited warranty begins on the original date of purchase, and is valid only on products purchased and used in the United States.

Woodstream® Corporation warrants its products to be free from defects in materials and workmanship for the warranty period by the original purchaser/user.

For warranty service, please contact our Customer Care (800) 953-5737. Please indicate the nature of the defect. Warranty service can only be performed by a Mosquito Magnet® Certified Service Center.

If Woodstream® Corporation determines there may be a defect, Woodstream® Corporation will issue a Return Goods Authorization (RGA) number. The defective unit or parts must be returned for warranty inspection using the RGA number, when applicable, as identification within (30) days of return authorization date. DO NOT return products to our factory without our prior consent, as they, as well as C.O.D. shipments will be refused. Woodstream® Corporation or agent, at its option, shall replace the unit, replace the defective part(s) and return such unit to you. Woodstream® Corporation's sole obligation and your exclusive remedy under this warranty shall be limited to such replacement.

Limitations and Exclusions:

The warranty shall not apply to problems arising from normal wear, or failure to adhere to the enclosed instructions. In addition, the foregoing warranty shall not apply to serial numbered products if the serial number has been removed or defaced; products subject to negligence, accident, improper operation, maintenance or storage; products damaged by circumstances beyond Woodstream® Corporation's control; or products modified (including, but not limited to modifications through the use of unauthorized parts or attachments) or repaired by anyone other than Woodstream® Corporation or its designee.

The foregoing warranty is exclusive and in lieu of all other warranties, express or implied, including without limitation the implied warranties of merchantability and fitness for a particular purpose. It shall not extend beyond the duration of the express warranty provided herein, and the remedy for violations of any warranty shall be limited to repair or replacement of the defective product pursuant to the terms contained herein. Woodstream® Corporation shall not be liable for any consequential or incidental damages whatsoever.

This warranty gives you specific legal rights and you may also have other legal rights which may vary based on location.



MOSQUITO MAGNET®



MOSQUITO MAGNET[®]



MOSQUITO MAGNET®

Systèmes de Défense Avancés Contre les Moustiques

DOMESTIQUE - GARDER HORS DE LA PORTÉE DES ENFANTS

LIRE L'ÉTIQUETTE AVANT D'UTILISER

Veillez conserver ce manuel d'utilisation pour référence ultérieure.

N° D'ENR. 29943 LPA



Chef de file en soutien 360°

- Service à la clientèle: 1-800-953-5737
- Assistance en ligne disponible
- Les lieux de service certifiés



Service à la
Clientèle
1-800-953-5737

INDEPENDENCE™

Woodstream Canada Corporation
25 Bramtree Court, Unit 1
Brampton, Ontario Canada L6S 6G2
Tel: (800) 800-1819
www.mosquitomagnet.com

Pour usage à l'extérieur seulement
1440-638

Manuel de l'utilisateur

GAS-FIRED
C  US 
LISTED
Gas Fired Insect
Control Equipment
47 WB

Bienvenue

Félicitations pour votre achat de Mosquito Magnet® Independence.

Soutenu par 18 années de recherche et de d'essais indépendants, il est scientifiquement prouvé que Mosquito Magnet® Independence capture et tue les moustiques.

Mosquito Magnet Independence est facile à utiliser. Dans ce manuel, vous apprendrez tout ce que vous avez besoin de savoir sur son fonctionnement, le meilleur emplacement du piège, la maintenance, l'entreposage et la garantie. Les clés du succès sont !'emplacement du piège, !'utilisation de l'appât adéquat pour votre région et de maintenance routine. Pour le taux de capture optimal, vous aurez besoin de changer le réservoir de propane et l'appât tous les 21 jours.

Notre service à la clientèle en ligne est disponible pour répondre à toutes vos questions concernant votre nouvel achat. N'hésitez pas à nous contacter ...

Service à la clientèle: 1-800-953-5737

Woodstream® Corporation
69 North Locust Street
Lititz, PA 17543
USA
www.mosquitomagnet.com

Brevets:

Etats Unis: Nos. 6,145,243; 6,286,249; 6,817,140;
6,840,005; 6,848,466; 6,892,492; 7,074,830; 7,243,458;
7,281,351; 7,293,387; 7,752,803; 7,987,631; 8,006,432;
8,753,110 et 8,898,953

Canada: Nos. 2,265,944 et 2,322,038

Europe: Nos. 1,011,324; 1,049,373 et 1,432,304 Autres brevets en instance

Fabrique aux Etats Unis

POUR VOTRE SÉCURITÉ

Si vous sentez une odeur de gaz:

- 1. Coupez l'alimentation de le gaz de l'appareil.*
- 2. Éteignez toute flamme nue.*
- 3. Ouvrez le couvercle.*
- 4. Si l'odeur persiste, appelez immédiatement votre fournisseur de gaz ou votre service d'incendie.*

POUR VOTRE SÉCURITÉ

- 1. Ne pas entreposer ni utiliser d'essence ou autres vapeurs et liquides inflammables à proximité de cet ou tout autre appareil.*
- 2. Une bouteille de propane non branchée ne doivent pas être entreposées à proximité de cet ou tout autre appareil.*



MOSQUITO MAGNET®

Table des matières

Consignes de sécurité	3c-4c
Pièces principales	5c
Consignes d'assemblage	6c
Assemblage du piège	
Installation	7c-9c
Consignes de chargement	
Emplacement du piège	
Installation d'un réservoir de propane	
Installation d'appât d'octenol	
Instructions	10c
Consignes de démarrage	
Consignes d'arrêt	
Lorsqu'il n'est pas utilisé	
Entreposage à la fin de la saison	
Pour des résultats optimaux	
Entretien	11c
Calendrier d'entretien	
Réservoir de propane Conseils de changement	
Dépannage	12c
Codes de défaut DEL	
Garantie	13c



Brevetés™ Technology à contre-courant

Fonctionnement du Mosquito Magnet® Independence™

Fonctionnement du Mosquito Magnet® Independence Les moustiques utilisent l'appât à longue portée dioxyde de carbone (CO₂) pour localiser les personnes. Une fois à proximité, les moustiques utilisent les appâts à courte portée comme les odeurs émises par la peau, pour déterminer quelle personne ils vont mordre. Le Mosquito Magnet Independence imite une personne par la conversion du propane en (CO₂), grâce à sa technologie brevetée de conversion catalytique, en combinaison avec un appât à courte portée.

Attirés par le (CO₂) et les appâts à courte portée, les moustiques sont attirés par le Mosquito Magnet Independence. Quand ils atteignent le piège, les moustiques sont aspirés dans un sac à insectes par notre technologie brevetée™ Counter Flow, où ils se déshydratent et meurent dans les 24 heures.

Le Mosquito Magnet Independence est silencieux et sans odeur. Lorsqu'il est correctement placé dans votre jardin, le piège commence à fonctionner immédiatement. Le Mosquito Magnet Independence ne vise que les moustiques, pas les insectes utiles comme les papillons, les abeilles ou les papillons de nuit.

Questions ou commentaires

S'il vous plaît contacter Woodstream Canada Corporation si vous avez des questions ou rencontrez des problèmes avec votre Mosquito Magnet® Independence:

1-800-953-5737

Woodstream Canada Corporation
25 Cour Bramtree, Unité 1
Brampton, Ontario Canada L6S 6G2
Tel: (800) 800-1819

www.mosquitomagnet.com

Modèle n° :	Independence™
N ° de série:	
Type de gaz:	Propane
Pression d'admission:	2,7 kPa (11 "WC)
Pression minimale d'alimentation eb gaz	2,7 kPa (11 "WC
Consommation thermique:	759 kJ / Hr. (759 Btu/ h)
Dégagement	50-60 cm (20 a 24 ")



MOSQUITO MAGNET®

Consignes de sécurité

S'il vous plaît lisez et suivez toutes les consignes et avertissements de sécurité.

Les enfants et les adultes doivent être avertis des risques liés à une température de surface élevée, et demeurer loin de celle-ci pour éviter des brûlures ou la combustion de leurs vêtements.

Les jeunes enfants doivent être supervisés soigneusement lorsqu'ils se trouvent à proximité de l'appareil de chauffage. **GARDER HORS DE LA PORTÉE DES ENFANTS.**

Les vêtements ou autres matières inflammables ne doivent pas être suspendus sur l'appareil de chauffage ou placés sur ou à proximité de celui-ci.

Note: Certaines ou toutes les consignes de sécurité suivantes concernant les appareils alimentés au propane peuvent s'appliquer à votre piège. Laissez le piège se refroidir pendant 5 minutes avant de redémarrer.

⚠ Avertissement: Toute installation, modification, altération, ou procédure de réparation ou d'entretien inadéquate peut causer des blessures ou des dégâts matériels. Lire les consignes d'installation, d'utilisation et d'entretien avant d'installer ou de réparer cet appareil.

⚠ Attention: Ce régulateur est réglé pour une pression de sortie de 2,7 kPa (11 po WC). La pression d'entrée minimum d'alimentation en gaz est de 2,7 kPa (11 po WC) du régulateur.

- Cet appareil n'est pas destiné à être installé dans ou sur les véhicules récréatifs et / OU des bateaux.
- L'alimentation en gaz doit être coupée à la bonbonne de gaz lorsque cet appareil n'est pas utilisé.
- L'installation doit être conforme aux codes locaux ou, en l'absence de codes locaux, au National Fuel Gas Code, ANSI Z223. 1-1998 pour les États Unis et au CANI-B149 pour le Canada.
- Pour vérifier la présence d'une fuite de gaz, mettre du l'eau, savonneuse autour du connecteur du régulateur et du tuyau de gaz. Si des bulles apparaissent, il y a une fuite de gaz.
- Inspectez le tuyau avant chaque utilisation de l'appareil. Si il est évident qu'il ya de l'abrasion ou une usure excessive, ou si le tuyau est coupé, il doit être remplacé avant de faire fonctionner l'appareil. La tuyauterie de remplacement doit être celle spécifiée par le constructeur.
- Le piège est équipé d'une étincelle intérieure. Le non respect de la procédure de démarrage peut nuire au démarrage du piège.
- L'installation et la réparation doivent être effectuées par une personne qualifiée (trouver des centres de service sur www.mosquitomagnet.com). L'appareil de chauffage doit être inspecté avant l'utilisation et au moins annuellement par une personne qualifiée. Un nettoyage plus fréquent peut être nécessaire. Il est impératif que le compartiment de contrôle, les brûleurs et les conduits d'air de l'appareil de chauffage soient gardés propres.



MOSQUITO MAGNET®

Consignes de sécurité

- Maintenir des espaces de dégagement adéquats de 50-60 cm (20 " - 24") autour des orifices de ventilation dans la chambre de combustion, les dégagements des matériaux combustibles, des dispositions d'accessibilité et d'alimentation en air de combustion et de ventilation. Garder la zone de piège claire et exempte de matériaux combustibles, essence et autres vapeurs et liquides inflammables. L'appareil ne doit pas être utilisé dans des endroits où des vapeurs inflammables ou des poussières explosives peuvent exister.
- Ne pas obstruer le conduit d'air de combustion et de ventilation.
- Garder les ouvertures de ventilation de l'enceinte de la bouteille libres et exemptes de débris.
- Nettoyer le piège avec un chiffon humide d'eau, si nécessaire.
- Une bonbonne de gaz de 9 kg (20 lb) maximum doit être utilisée.
- La bonbonne de gaz doit être munie d'un robinet d'arrêt au bout des conduits d'écoulement de la bonbonne de gaz qui est conçu pour une connexion n° 510 selon la norme sur les raccords d'entrée et de sortie de vanne de bouteilles à gaz comprimé, ANSI/CGA-V- 1-1977.
- Le système d'alimentation de la bonbonne de gaz doit être adapté pour le retrait de vapeur et le cylindre doit avoir un collet pour protéger le robinet de la bouteille.
- La bonbonne de gaz utilisée doit être fabriquée et identifiée conformément aux spécifications pour les bouteilles de propane de la Norme nationale du Canada CAN/CSA-B339.
- Le piège doit être utilisé à l'extérieur seulement dans un espace bien aéré et ne doit pas être utilisé dans un bâtiment, un garage ou tout autre endroit fermé.
- La bonbonne de gaz doit être débranchée et retirée de l'appareil, si l'appareil est entreposé à l'intérieur.
- Les bonbonnes de gaz doivent être entreposées à l'extérieur dans un endroit bien aéré, hors de la portée des enfants.
- Les cylindres débranchés doivent comporter des fiches de vannes filetéées bien installées et ne doivent pas être entreposés dans un bâtiment, un garage ou tout autre endroit fermé.
- Le régulateur de pression et le raccord de tuyau fournis avec cet appareil doivent être utilisés pour la connexion à la bonbonne de gaz. Le remplacement des régulateurs de pression et des raccords de tuyaux doit être spécifié par le constructeur.
- Éviter l'usage inadéquat des rallonges. Garder les connexions loin de l'humidité et d'éviter d'endommager le cordon.
- Si le cordon d'alimentation est endommagé, il doit être remplacé par le fabricant ou son agent de service ou une personne qualifiée afin d'éviter tout danger.

S'il vous plaît contacter le service client
si vous avez des questions au:


1-800-953-5737

ou visitez www.mosquitomagnet.com




MOSQUITO MAGNET®

Pièces principales




Pieces incluses


Mosquito Magnet® appât à l'octenol Mosquito
(Appât Ajouté)



Sac iJ insectes




4 Piles C



Consignes D'assemblage


Assemblage du piège:

Étape 1




Placer la base a l'envers sur une surface plane, déplier la jambe support en U jusqu'à ce qu'il se verrouille en place.

Étape 2



Tourner la base et les pieds a l'endroit, et placer la perche de maintien dans la cavité sur la base.


Étape 3



Placer la tête mecanique du piège dans la perche.
Appuyer fermement avec les deux mains pour la fixer.


Lorsque l'assemblage est terminé, le devant de la tête de pompe/trompette devrait être le plus éloigné des roues dans la même direction que les pieds en forme de U.

Étape 4




Ouvrir la porte des piles à l'arrière du piège.

Étape 5



Placer quatre (4) piles "C" dans la cage des piles et insérer dans l'ouverture.

Étape 6



Fermer la porte des piles pour terminer (s'enclenche).
Les piles durent toute la saison.



MOSQUITO MAGNET®


Installation

Installation Sac a insectes:

Soulever le couvercle en plastique transparent et verrouiller le support de retenue en plastique du sac à insectes dans la partie avant du compartiment.

Fermer le couvercle en plastique lorsque terminé.


Note: Les boucles du tissu s'accrochent aux perches en plastique, ce qui permet au sac à insectes de s'élargir au maximum.



Les Sacs à insectes se verrouillent en avant du compartiment.

Emplacement du piège

1. Déterminer la direction du vent dominant. Vérifiez les conditions météorologiques locales si vous n'êtes pas sûr.
2. Se tenir au centre de la zone que vous essayez de protéger et de se tourner vers le vent dominant.
3. Le positionnement correct du piège sera 9-12 m (30 à 40 pieds) en avant de soi, dans 1,5 à 1,8 m (5-6 pieds) de l'habitat des moustiques (c.-à-eaux stagnantes, de buissons, massifs de fleurs, la limite forestière, le marais). Veiller à ce que le piège ne soit pas directement contre tout blocage tels que les bâtiments, les clôtures, etc.
4. Il est recommandé de placer le piège à l'ombre.
5. Ne pas placer le piège directement au-dessus d'une source d'eau (arroseurs, tuyaux, etc.)
6. Le piège doit être placé sur un terrain plat pour éviter d'être renversé ou que la distribution de propane ne soit pas uniforme.
7. Voir notre site web à www.mosquitomagnet.com pour construire votre diagramme propre cour.



Installation

Installation d'un réservoir de propane


1. Après avoir trouvé l'emplacement idéal du piège, placer le réservoir de propane dans le berceau moulé.
2. Après s'être assuré que le réservoir est bien fermé, fixer le tuyau du régulateur de propane au réservoir de propane. Bien serrer à la main. **Ne pas utiliser, d'outils.**
3. Activer le propane en tournant la vanne lentement dans le sens anti-horaire. Prendre soin de ne pas tourner trop vite pour éviter d'enclencher le clapet antiretour dans le régulateur.

⚠ NE PAS DÉPLACER LE PIÈGE LORSQUE LE RÉSERVOIR EST FIXE!
AVANT DE DÉPLACER LE PIÈGE POUR NE PAS ENDOMMAGER LE RÉGULATEUR ET/OU LE PIÈGE LES DOMMAGES CAUSÉS PAR LE NON-RESPECT DE CES CONSIGNES NE SONT PAS COUVERTS PAR LA GARANTIE.


Installation d'appât d'octenol

Voir l'étiquette du Mosquito Magnet® appât à moustiques à base d'octenol Mosquito pour les instructions de l'installation, de l'utilisation, de l'entreposage et de l'élimination.


Étape 1 - Poser de la bouteille de propane



Étape 2 - Brancher le régulateur



Étape 3. Ouvrir lentement le robinet



MOSQUITO MAGNET®

Installation

Octenol Attractant Installation

1. Locate Mosquito Magnet® Octenol Biting Insect Attractant. Remove mosquito attractant packet from bag. Carefully peel back foil cover
2. Locate the octenol carrier compartment inside the plume tube. Turn cap counter-clockwise about 1/8 turn. Remove end cap.
3. Place the open packet of mosquito attractant into the carrier compartment.
4. Replace end cap on carrier compartment. Be sure to align cap's "feet" with grooves inside carrier compartment. Secure cap by turning clockwise until it clicks (about 1/8 turn).

Precautionary Statements

Hazards to Humans and Domestic Animals.

Caution: Harmful if swallowed. Avoid contact of skin, eyes or mouth with the evaporation holes. Wash hands before eating, drinking, chewing gum, using tobacco or using bathroom facilities.

First Aid

If swallowed

- Call poison control center or doctor immediately for treatment advice.
- Have person sip a glass of water if able to swallow.
- Do not induce vomiting unless told to do so by the poison control center or doctor.
- Do not give anything by mouth to an unconscious person.

If on skin or clothing

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

If in eyes

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

If inhaled

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible.
- Call a poison control center or doctor for treatment advice.

Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

Environmental Hazards: Do not apply directly to water. Do not contaminate water when disposing of equipment washwaters or rinsate.

Directions for Use

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

Replace cartridge every 21 days* (Note: After 21 days of use, cartridge appears the same; however, it will no longer be effective as the octenol will have been released.)

*Based on release rate studies conducted at a constant ambient air temperature of 80° F for 21 days. Octenol release from this product will be more rapid at higher ambient air temperature.

Storage & Disposal

Do not contaminate water, food or feed by storage or disposal.

Storage: Store unopened attractant cartridge in a cool, dry place. Discard outer plastic bag in trash.

Disposal: Do not reuse attractant cartridge. Dispose of used attractant cartridge in the trash.

Step 1



Step 2



Step 3



Step 4



MOSQUITO MAGNET®

Instructions

*** LIRE LE MANUEL AVANT DE COMMENCER****

Consignes de démarrage

Il est recommandé de lire le manuel en entier avant de démarrer le piège Mosquito Magnet® Independence.

1. Insérer l'appât dans le compartiment selon les instructions dans l'emballage attractif.
2. Installer 4 piles "C" dans le compartiment arrière.
3. Connecter le régulateur au réservoir de propane (voir page 7c).
4. Tourner lentement le robinet du réservoir de propane.
5. Pousser interrupteur ON / OFF sur la position ON. Le voyant DEL deviendra orange indiquant le réchauffement. Après 15 à 25 minutes, le voyant DEL du piège deviendra vert indiquant que le piège fonctionne à pleine capacité.

Consignes d'arrêt

Pour arrêter le Mosquito Magnet® Independence, fermer simplement la vanne du réservoir de propane et mettre l'interrupteur à la position OFF.

Lorsqu'il n'est pas utilisé

Si l'appareil n'est pas utilisé, le gaz doit être coupé à la bouteille de gaz. L'entreposage de cette unité à l'intérieur n'est autorisé que si la bouteille est débranchée et enlevée. Les bouteilles doivent être entreposées à l'extérieur, hors de portée des enfants et ne doivent pas être entreposées dans un bâtiment, un garage ou tout autre endroit fermé.

Entreposage à la fin de la saison

Référez-vous à la section consignes d'arrêt ci-dessus avant de fermer la vanne de réservoir de propane et débrancher le régulateur. Fermez la vanne de réservoir de propane et débranchez le régulateur. En outre, débranchez la pile, mais veillez à ne pas retirer la pile du piège.

Tous les Mosquito Magnet® appâts à moustiques à base d'octenol ouverts doivent être enlevés et jetés. Voir l'étiquette d'appât pour les instructions d'élimination. Le sac à insectes devraient également être mis au rebut avant de ranger le piège.

ENTREPOSAGE: Mosquito Magnet® Independence™ devrait être entreposé à l'intérieur dans un garage ou un abri dans la mort-saison. Couvrir la trompette afin d'éviter que les insectes ne s'y nichent. Couvrir l'appareil avec le couvercle du piège disponible à www.mosquitomagnet.com ou avec une bâche et bien fixer la base pour éviter toute accumulation de la poussière, de toiles d'araignées et d'autres débris.

Pour des résultats optimaux fonctionner 24 heures / jour

- Laisser le piège se refroidir pendant 5 minutes avant de redémarrer.
- Ne vaporisez jamais d'insecticide dans le piège ou alentours.
- Le piège peut être laissé en marche sous la pluie.
- Si vous utilisez des composés de chaux ou d'engrais, assurez-vous d'arrêter d'abord le piège pour empêcher la poussière ou de brouillard de vaporisation d'être attiré dans le piège et le sac à insectes ce qui obstruerait le sac.

AVERTISSEMENT: Toute installation, modification, altération, ou procédure de réparation ou d'entretien inadéquate peut causer des blessures ou des dégâts matériels. Lire les consignes d'installation, d'utilisation et d'entretien avant d'installer ou de réparer cet

Attention: Le régulateur de pression de gaz fourni avec cet appareil doit être utilisé. Ce régulateur est réglé pour une pression de sortie de 2,7 kPa (11 po WC).

L'alimentation en gaz doit être coupée à la bonbonne de gaz lorsque cet appareil n'est pas utilisé.

Chef de file en soutien pour /es clients 360 °

- Service à la clientèle: 1-800-953-5737
- Enregistrement du produit Disponible en ligne
- Les lieux de services certifiés - Informations disponibles à www.mosquitomagnet.com



MOSQUITO MAGNET®

Entretien

Calendrier d'entretien

- **Cycle d'entretien de 21 jours - pour une performance optimale de maximiser joint.**

- Remplir le réservoir de propane. (La réserve dure environ 21 jours lorsque l'appareil fonctionne 24 heures / jour).
- Remplacer la cartouche d'appât de courte portée. Voir l'étiquette du Mosquito Magnet® appât à moustiques à base d'octenol pour connaître les consignes.

- *Essuyer périodiquement l'extérieur du piège avec un chiffon propre et humidifié avec de l'eau.*
- *Chargez votre pile pendant 24 heures au début de la saison.*

Réservoir de propane Conseils de changement

En fixant la poignée du régulateur au réservoir à près un changement de réservoir, s'assurer de complètement serrer la poignée du régulateur au réservoir. Il n'est pas nécessaire d'utiliser des outils, mais il faut tourner la poignée aussi loin que possible à la main. Ensuite, la desserrer de 1 / 4 de tour, puis la serrer de nouveau pour maximiser l'herméticité.

Le but de ceci consiste à bien enclencher le régulateur dans le réservoir. Si le régulateur n'est pas bien enclenché, le débit de gaz peut être limité au point où le piège indiquera un code signifiant qu'il n'y a plus de gaz. Le cas échéant, appuyer sur le bouton «off», fermer la vanne du réservoir, et retirer le régulateur du réservoir. Fixer le régulateur et essayer de nouveau.



Guide de dépannage

Problème	Causes possibles	Solutions
<p>L'appareil ne démarre pas</p> <p>Le voyant DEL rouge clignote à intervalles de 7 secondes</p>	<ol style="list-style-type: none"> Réservoir de propane peut être vide. Si le réservoir de propane est neuf et a été récemment rempli il doit être purgé. Une connexion pourrait être desserrée. 	<ol style="list-style-type: none"> Peser le réservoir et comparer ce poids au poids vide inscrit sur le réservoir. Apporter le réservoir à un centre de remplissage. Il peut y avoir de l'air dans la conduite de carburant. Faire vider le réservoir. Conseil: Si un autre dispositif alimenté au propane est raccordé à un réservoir standard de 9 kg (20 lb), essayer de raccorder le réservoir au Mosquito Magnet® Independence pour vérifier si le problème est causé par le réservoir. Vérifiez toutes les connexions. Assurez-vous que la vanne du réservoir de propane est complètement ouverte.
<p>L'appareil ne fonctionne pas constamment</p>	<ol style="list-style-type: none"> Les causes possibles 1 et 3 ci-dessus peuvent s'appliquer. Le régulateur n'est pas pleinement engagé. 	<ol style="list-style-type: none"> Suivez les étapes ci-dessus 1 et 3. Voir les conseils sur le changement de réservoir à la page 7c.
<p>Capture rare ou inexistante</p>	<ol style="list-style-type: none"> Les moustiques ne peuvent pas être encore sortis. Problème d'emplacement du piège. Le contre-courant peut être perturbé. 	<ol style="list-style-type: none"> Vérifier que la température est constamment supérieure à 10°C (50 °F). Suivre les étapes de la section Emplacement du piège dans le manuel de l'utilisateur. Faire fonctionner l'appareil en continu 24 heures / jour, 7 jours / semaine. Le débit d'air peut être restreint. Appeler le service à la clientèle au: 1-800-953-5737.
<p>Le voyant DEL rouge / vert clignotant à intervalles de 7 secondes</p>	<ol style="list-style-type: none"> Température élevée. 	<ol style="list-style-type: none"> Arrêter le piège et le laisser refroidir pendant 1/2 heure. Redémarrer. Si le code est toujours affiché, appeler le service à la clientèle au: 1-800-953-5737.
<p>Le voyant DEL rouge/orange clignotant à intervalles de 7 secondes</p>	<ol style="list-style-type: none"> Tension faible des piles. 	<ol style="list-style-type: none"> Assurez-vous que les 4 piles C sont correctement installés et neuves. S'assurer que le connecteur de cages en batterie est correctement installé. Après plusieurs tentatives infructueuses, le remplacer par 4 nouvelles piles C.
<p>Deux voyants DEL rouge clignote à intervalles de 7 secondes</p>	<ol style="list-style-type: none"> Panne de la thermistance. 	<ol style="list-style-type: none"> Communiquez avec le Service à la clientèle au: 1-800-953-5737.
<p>Voyant DEL rouge solide défaut électrique</p>	<ol style="list-style-type: none"> Panne électrique. 	<ol style="list-style-type: none"> Communiquez avec le Service à la clientèle au: 1-800-953-5737.



MOSQUITO MAGNET®

Garantie limitée

Garantie limitée

Cette garantie, (1) an à partir de la date d'achat, est offerte uniquement à l'acheteur / utilisateur initial des produits.

Woodstream Canada Corporation garantit que ses produits sont exempts de défauts de matériaux et de fabrication pour la période de garantie par l'acheteur / utilisateur initial.

Pour une réparation sous garantie, s'il vous plaît communiquer avec notre service à la clientèle (800) 953-5737. S'il vous plaît indiquer la nature du défaut.

Si Woodstream Canada Corporation détermine qu'il peut y avoir un défaut, Woodstream Canada Corporation émettra un numéro d'autorisation de retour de marchandise (ARM). L'unité ou les pièces défectueuses doivent être retournées pour vérification de garantie, en utilisant le numéro d'autorisation (ARM), le cas échéant, à titre d'identification au sein de (30) jours suivant la date d'autorisation de retour. NE PAS retourner les produits à notre usine sans notre consentement préalable, car ils, seront refusés tout comme les envois payables sur livraison. Woodstream Canada Corporation ou un agent peut, à sa discrétion, remplacer l'appareil, les pièces défectueuses, et retourner l'appareil à son propriétaire. La seule obligation de Woodstream Canada Corporation et votre seul recours sous cette garantie est limitée à un tel remplacement.

Limitations et exclusions:

La garantie ne s'applique pas aux problèmes causés par l'usure normale, au non-respect des consignes ci-jointes. En outre, la garantie qui précède ne s'applique pas aux numéros de série des produits dont le numéro de série a été enlevé ou rendu illisible; aux produits soumis à une négligence, à un accident, à un usage, un entretien ou un entreposage inadéquat, aux produits endommagés par des circonstances indépendantes de la volonté de Woodstream Canada Corporation, ou aux produits modifiés (y compris, mais sans s'y limiter à des modifications réalisées suite à l'utilisation de pièces ou accessoires non autorisés) ou réparés par quiconque autre que Woodstream Canada Corporation ou son représentant.

La présente garantie est exclusive et remplace toute autre garantie, expresse ou implicite, y compris, sans limitation, les garanties implicites de qualité marchande et d'adéquation à un usage particulier. Elle ne doit pas s'étendre au-delà de la durée de la garantie expresse indiquée dans les présentes, et le recours en cas de violation de toute garantie est limitée à la réparation ou le remplacement du produit défectueux conformément aux modalités contenues dans les présentes. Woodstream Canada Corporation ne pourra être tenu responsable pour tous dommages directs ou indirects que ce soit.

Cette garantie vous donne des droits légaux spécifiques et vous pourriez également bénéficier d'autres droits légaux qui peuvent varier selon l'emplacement.



MOSQUITO MAGNET®